# Product data sheet
## Characteristics

# QO315
## Mini circuit breaker, QO, 15A, 3 pole, 120/240VAC, 10kA, plug in mount



## Main

| | |
|---|---|
| Product | Miniature circuit-breaker |
| Range | QO |
| Current Rating | 15 A |
| Voltage Rating | 120/240 V AC<br>240 V AC<br>120 V AC |
| Mounting Type | Plug-in |
| Number of Poles | 3P |
| Circuit Breaker Type | Standard |
| Ratings | HACR rated |
| Electrical Connection | Pressure plate |

## Complementary

| | |
|---|---|
| Interrupt Rating | 10 KA 120/240 V AC 50/60 Hz<br>10 KA 240 V AC 50/60 Hz<br>10 kA 120 V AC 50/60 Hz |
| Number of Panel Spaces | 3 |
| Wire Size | AWG 14...AWG 8 copper or aluminium |
| Tightening Torque | 44.25 lbf.in (5 N.m) 0.02…0.04 in² (10…25 mm²) (AWG 8...AWG 2) |
| Height | 2.99 in (76 mm) |
| Width | 2.24 in (57 mm) |
| Depth | 2.91 in (74 mm) |
| Net Weight | 0.80 lb(US) (0.363 kg) |

## Environment

| | |
|---|---|
| Certifications | UL Listed<br>CSA |
| Ambient Rating | 104 °F (40 °C) |

## Ordering and shipping details

| | |
|---|---|
| Category | 00012-QO 3 POLE CIRCUIT BREAKER |
| Discount Schedule | DE2A |
| GTIN | 785901400646 |
| Returnability | Yes |
| Country of origin | MX |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.30 in (5.842 cm) |
| Package 1 Width | 3.00 in (7.62 cm) |
| Package 1 Length | 3.20 in (8.128 cm) |
| Package 1 Weight | 12.80 oz (363.0 g) |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 3 |
| Package 2 Height | 3.30 in (8.382 cm) |
| Package 2 Width | 3.00 in (7.62 cm) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|---|---|
| Package 2 Length | 6.80 in (17.272 cm) |
| Package 2 Weight | 2.41 lb(US) (1.093 kg) |
| Unit Type of Package 3 | CAR |
| Number of Units in Package 3 | 36 |
| Package 3 Height | 3.40 in (8.636 cm) |
| Package 3 Width | 14.30 in (36.322 cm) |
| Package 3 Length | 21.50 in (54.61 cm) |
| Package 3 Weight | 30.60 lb(US) (13.88 kg) |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Halogen content performance | Halogen free product |

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |