# Product data sheet
## Characteristics

# QO320GFI
## Mini CB, QO, 20 A, 3P, 208Y/120 V, 10 kA, Plug in, GFI

Product availability : Stock - Normally stocked in distribution facility

Price** : 791.00 USD



## Main

| | |
|---|---|
| Product | Miniature circuit-breaker |
| Range | QO |
| Current Rating | 20 A |
| Voltage Rating | 208Y/120 V AC |
| Mounting Type | Plug-in |
| Number of Poles | 3P |
| Circuit Breaker Type | Ground fault protecting class A 6 mA |
| Ratings | Not rated |
| Electrical Connection | Pressure plate |

## Complementary

| | |
|---|---|
| Inturrupt Rating | 10 kA 208Y/120 V AC 50/60 Hz |
| Number of Panel Spaces | 3 |
| Wire Size | AWG 14...AWG 8 copper<br>AWG 12...AWG 8 aluminium |
| Tightening torque | 40.71 lbf.in (4.6 N.m) 0.00…0.02 in² (2.5…10 mm²) AWG 16...AWG 14)<br>40.71 lbf.in (4.6 N.m) 0.01…0.03 in² (4…20 mm²) AWG 12...AWG 4) |
| Height | 104.65 mm (4.12 in) |
| Depth | 73.91 mm (2.91 in) |
| Width | 57.15 mm (2.25 in) |

## Environment

| | |
|---|---|
| Certifications | UL listed<br>CSA |
| Ambient Rating | 104 °F (40 °C) |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Ordering and shipping details

| | |
|---|---|
| Category | 00103 - QO 2 POLE GFI CB 40-60A |
| Discount Schedule | DE2A |
| GTIN | 00785901298588 |
| Package weight(Lbs) | 0.63 kg (1.38 lb(US)) |
| Returnability | Yes |
| Country of origin | MX |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Compliant<br>EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration<br>Product out of China RoHS scope. Substance declaration for your information. |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |