SIEMENS

B315HH



Siemens HBL breakers provide easy bolt-on connections in Siemens panelboards. Siemens offers 3 AIC ratings for these breakers: BL at 10K AIC, BLH at 22K AIC, and HBL at 65 K AIC. They are available in 10-125 Amp, with 1, 2 and Triple Poles. All circuit breakers are designed to sense when an over current occurs, measure the amount of over current and lastly, act by tripping quickly enough to prevent damage to itself and associated conductors.

- 40?C calibration
- 65K AIC series rating
- HACR rated
- Panel board mounting
- UL listed

Documents

Speed Fax Sections 1

Speed Fax Sections 2

Certificates

Standard	UL LISTED / CSA / NOM CERTIFIED

Electricity

Continuous current / rated value	15 A
Voltage / between phase and phase / rated value	240 V
Supply voltage frequency / rated value / 50/60 Hz	1

General Technical Data

Suitability for operation	ELECTRICAL DISTRIBUTION
Number of poles	3

Mechanical Design

Design of the product	HBL
Size of the circuit-breaker	BL (125A)
Design of the overload release	THERMAL - MAGNETIC
Height [in]	3.75 in
Width [in]	3 in
Depth [in]	3 in

Speed Fax Sections 3

Information and Instruction 4

Cut Sheets 5

Cut Sheets 6

Model

Product feature	65kA INTERRUPT
Type of electrical connection	BOLT-ON
Type of connectable conductor cross-sections / at AWG conductors / for load-side outgoing feeder / single or multi-stranded	14 - 12AWG (CU) / 12 - 10AWG (AL)
Type of mounting panel	PANELBOARD
Product brand name	SIEMENS

Delivery Information

Export Control Class	AL : N / ECCN : EAR99
Net Weight	0.975
Product_Dimensions (LxWxH)	7.0X9.0X13.0

Additional Product Information

EAN/UPC	50783643264200
Country of Origin	MX, US
Commodity Code	8536200020
RoHS Compliance	*DQ

Product Selector Information

Amperage	15
Connection Style	BOLT ON STYLE
Frequency	60
Poles	3
UL Interrupt Rating (kA)	65
UL Voltage (V)	240