ELECTRONIC MINI CIRCUIT BREAKERS

eBL Circuit Breaker

1 - 2-pole; 10A - 60A
UL Listed, HACR Rated
usa.siemens.com/resibreakers




1-Pole Combination Type AFCI



2-Pole Combination Type AFCI

Combination Type AFCI

Amp Rating	Poles	BAF2 (10kAIC)	BAFH2 (22kAIC)	HBAF2 (65kAIC)
15	1	BA115AFC	BA115AFCH	BA115AFCHH
20	1	BA120AFC	BA120AFCH	BA120AFCHH
Amp Rating	**Poles**	**BAF (10kAIC)**	**BAFH (22kAIC)**	**–**
15	2	B215AFC	B215AFCH	–
20	2	B220AFC	B220AFCH	–



1-Pole Dual Function AFCI/GFCI

Dual Function AFCI/GFCI

Amp Rating	Poles	BFGA2 (10kAIC)	BFGAH2 (22kAIC)	HBFGA2 (65kAIC)
15	1	B115DF	B115DFH	B115DFHH
20	1	B120DF	B120DFH	B120DFHH



1-Pole Equipment Protection



2-Pole Equipment Protection

Ground-Fault Circuit Interrupters (GFCI) (5mA)

Breaker Type	Amp Rating	10kAIC	22kAIC	65kAIC
BLF2/BLHF2/ HBLF2	15	BF115A	BF115AH	BF115AHH
	20	BF120A	BF120AH	BF120AHH
	25	BF125A	BF125AH	BF125AHH
	30	BF130A	BF130AH	BF130AHH
BLFB/BLHFB/ HBLFB	15	B215GF	B215GFH	B215GFHH
	20	B220GF	B220GFH	B220GFHH
	30	B230GF	B230GFH	B230GFHH
BLF/BLHF	40	BF240A	BF240AH	–
	50	BF250A	BF250AH	–
	60	BF260A	BF260AH	–

SIEMENS



1-Pole Equipment Protection



2-Pole Equipment Protection

Ground-Fault Circuit Interrupters (GFCI) (30mA)

Breaker Type	Amp Rating	10kAIC	22kAIC	65kAIC
BLE2/BLEH2/ HBLE2	15	BE115	BE115H	–
	20	BE120	BE120H	–
	30	BE130	BE130H	–
BLEB/BLEHB/ HBLEB	15	B215EG	B215EGH	B215EGHH
	20	B220EG	B220EGH	B220EGHH
	30	B230EG	B230EGH	B230EGHH
BLE/BLEH	40	BE240	BE240H	–
	50	BE250	BE250H	–
	60	BE260	BE260H	–

Standards:

AFCI Circuit Breakers

cULus 489 and cULus 1699

Class A GFCI Circuit Breakers (5mA)

UL 489 and UL 943

CSA C22.2 No. 144.1

NMX-J-520-ANCE

Equipment GFCI Circuit Breakers

UL 489 and 1053

CSA C22.2 No. 144

Dual Function Devices (AFCI/GFCI)

UL 489, UL 1699 and UL 943

CSA C22.2 No. 144.1-06 and 5-16

Pressure Wire Connectors
Load Side terminal factory installed only

Breaker Type	Amp Rating	Cables per Lug	No. of Poles	Wire Range
BAF, BAFH, HBAF, BFGA, BFGAH, HBFGA, BLF, BLFH, BLE & BLEH	15 - 20	1	1, 2, 3	#14 - #10 AWG Cu
		1	1, 2, 3	#12 - #10 AWG Al.
	25 - 35	1	1, 2, 3	#10 - #8 AWG Cu.
		1	1, 2, 3	#10 - #6 AWG Al.
	40 - 50	1	1, 2, 3	#8 - #6 AWG Cu.
		1	1, 2, 3	#8 - #4 AWG Al.
	55 - 60	1	1, 2	#6 - #4 AWG Cu.
		1	1, 2	#6 - #4 AWG Al.

External Accessories

Description	Catalog Number	No. of Poles
Padlocking Device	ECPLD1	1
	ECPLD1R	1
	ECPLD2	2
	ECPLD2R	2
Handle Blocking Device	ECBX231M	1

Legal Manufacturer

Siemens Industry, Inc.
3617 Parkway Ln
Peachtree Corners, GA 30092
United States of America

Telephone: +1 (800) 333-7421
www.usa.siemens.com/resibreakers

Order No. CBDS-EBL01-1224
© 12.2024, Siemens Industry, Inc.

This document contains a general description of available technical options only, and its effectiveness will be subject to specific variables including field conditions and project parameters. Siemens does not make representations, warranties, or assurances as to the accuracy or completeness of the content contained herein. Siemens reserves the right to modify the technology and product specifications in its sole discretion without advance notice.

SIEMENS