SIEMENS

Non-Fused Air Conditioning Disconnects





Features	Benefits
■ Ample Wiring Space	■ The larger enclosure allows for ample wiring space.
■ Rugged Design	■ Manufactured with powder coated G90 galvanized steel for fade, scratch and corrosion resistance.
■ Numerous Knockouts	■ All (6) knockouts are easy to remove. The sidewall knockouts provide access from the sides of the device. Every knockout has 1/2", 3/4" and 1" provisions.
■ Raised Mounting Embosses	■ (4) Raised mounting embosses keep the unit away from the wall, preventing dirt build-up. The upper mounting hole is shaped to be used as a hanger.
■ Copper Conductors	■ Copper current carrying part allows for a cooler, longer lasting operation.
■ Pullout Switch	■ The pullout switch design allows you to safely and easily de-energize the load terminals.
■ Removable Door	■ The easily removable door makes it possible to wire the device with absolutely no interference.
■ Meets National Electrical Code® Requirements	■ Siemens air conditioning disconnects provide the ideal means to comply to articles 440-14 and 110-3(b) of the 1999 National Electrical Code®.

UL Listed, NEMA Type 3R Enclosure — 240 Volts

Catalog Number	Ampere Rating	Maximum Horsepower	Disconnect Type	Std. Pkg.
WN2060	60	10	Non-Fusible Pullout	6

® National Electrical Code is a registered trademark of the National Fire Protection Association.
® UL is a registered trademark of Underwriters Laboratories, Inc.