SIEMENS

Data sheet US2:WP2211



Siemens Low Voltage's Multi-Family Metering Line of PAK Metering: Standard 125A as part of the PAK Metering: Standard 125A Group. Type: UNI-PAK Features: NO BYPASS Appn: GARDEN - STYLE Std: UL-50,67,414 V. Rating: 120/240V A. Rating: 200A phase: 1PH size: 7.25 x 14.05 x 27.140 No. Of Cutouts: 7 Cutout Size: 2X1/2", 1 x (1-1/2,1-1/4,1"), 2 x (,2,1-1/2,1-1/4,1"), 1 x (3,2-1/2,2,1-1/2,2"), 1X4" Cable Entry: TOP OR BOTTOM FEED Terminal: 3X2 STUDS. Insulated.Appn:. Wall Mounted. Enclosure: RING

cable entry type	TOP OR BOTTOM FEED
fastening method	WALL MOUNTED
suitability for operation	GARDEN-STYLE
Electricity	
ampacity	200 A
Model	
product brand name	Siemens
product type designation	UNI-PAK
special product feature	NO BYPASS
Mechanical Design	
design of the terminal strip	3X2 STUDS
General product approval	
certificate of suitability	UL-50;67;414

last modified: 3/9/2020

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens