SIEMENS

## Data sheet US2:WP4411RJ



Siemens Low Voltage's Multi-Family Metering Line of PAK Metering: Standard 125A as part of the PAK Metering: Standard 125A Group. Type: UNI-PAK Features: NO BYPASS Appn: GARDEN - STYLE Std: UL-50,67,414 V. Rating: 120/240V A. Rating: 400 A phase: 1PH size: 9.00 x 26.74 x 48.630 No. Of Cutouts: 11 Cutout Size: 1 x (1/2,3/4,1,1-1/4"), 6 x (2-1/2,2,1-1/2,1-1/4,1"), 2 x (4,3-1/2,3,2-1/2,2"), 2X4" Cable Entry: TOP OR BOTTOM FEED Terminal: 3X2 STUDS. Insulated.Appn:. Wall Mounted. Enclosure: RINGLESS

| | |
|---|---|
| **General technical data** | |
| cable entry type | TOP OR BOTTOM FEED |
| fastening method | WALL MOUNTED |
| suitability for operation | GARDEN-STYLE |
| **Electricity** | |
| ampacity | 400 A |
| **Model** | |
| product brand name | Siemens |
| product type designation | UNI-PAK |
| special product feature | NO BYPASS |
| **Mechanical Design** | |
| design of the terminal strip | 3X2 STUDS |
| **General product approval** | |
| certificate of suitability | UL-50;67;414 |

**last modified:** 5/9/2023


Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens