High CRI Filament Lamps

TCP's LED Filament High CRI Standard Lamps combine the beauty and style of traditional lamps with visual aesthetics of exposed filaments and superior LED energy savings. Exclusive technology provides unmatched longevity and perfect dimming down to 5%. High CRI output provides outstanding color consistency and beautiful, natural color rendering.

Features & Benefits

- High CRI value provides excellent color rendering results and color consistency while maintaining uniformity
- Uses up to 85% less energy than halogen and incandescent lamps
- UL approved for damp and enclosed fixtures
- Smooth, uniform dimming down to 5%
- All-glass construction

Specifications

Color Temperatures 2700K, 3000K, 4000K, 5000K
Input Line Voltage ..... 120 VAC
Frequency 50/60HZ
Lamp Life (Rated) ..... 15,000 hours
Minimum Starting Temp ..... -30°C
Maximum Operating Temp ..... 40°C
CRI 95
Base E12, E26

	ITEM #	DESCRIPTION	VOLTAGE	WATTS	WATT EQUIV.	LUMENS	LPW	BASE	CCT	CRI	FINISH	CASE QTY.
4.5W Filament A19 – Dimmable • E26 Base • 15,000 Rated Life												
	FA19D4027E26SCL95	LED 4.5W A19 CLEAR 95 CRI 27K	120V	4.5	40	450	100	E26	2700K	95	CLEAR	12
	FA19D4027E26SFR95	LED 4.5W A19 FROST 95 CRI 27K	120V	4.5	40	450	100	E26	2700K	95	FROST	12
	FA19D4030E26SCL95	LED 4.5W A19 CLEAR 95 CRI 30K	120V	4.5	40	450	100	E26	3000K	95	CLEAR	12
	FA19D4030E26SFR95	LED 4.5W A19 FROST 95 CRI 30K	120V	4.5	40	450	100	E26	3000K	95	FROST	12
	FA19D4040E26SCL95	LED 4.5W A19 CLEAR 95 CRI 40K	120V	4.5	40	450	100	E26	4000K	95	CLEAR	12
	FA19D4040E26SFR95	LED 4.5W A19 FROST 95 CRI 40K	120V	4.5	40	450	100	E26	4000K	95	FROST	12
	FA19D4050E26SCL95	LED 4.5W A19 CLEAR 95 CRI 50K	120V	4.5	40	450	100	E26	5000K	95	CLEAR	12
	FA19D4050E26SFR95	LED 4.5W A19 FROST 95 CRI 50K	120V	4.5	40	450	100	E26	5000K	95	FROST	12
8W Filament A19 – Dimmable • E26 Base • 15,000 Rated Life												
	FA19D6027E26SCL95	LED 8W A19 CLEAR 95 CRI 27K	120V	8	60	800	100	E26	2700K	95	CLEAR	12
	FA19D6027E26SFR95	LED 8W A19 FROST 95 CRI 27K	120V	8	60	800	100	E26	2700K	95	FROST	12
	FA19D6030E26SCL95	LED 8W A19 CLEAR 95 CRI 30K	120V	8	60	800	100	E26	3000K	95	CLEAR	12
	FA19D6030E26SFR95	LED 8W A19 FROST 95 CRI 30K	120V	8	60	800	100	E26	3000K	95	FROST	12
	FA19D6040E26SCL95	LED 8W A19 CLEAR 95 CRI 40K	120V	8	60	800	100	E26	4000K	95	CLEAR	12
	FA19D6040E26SFR95	LED 8W A19 FROST 95 CRI 40K	120V	8	60	800	100	E26	4000K	95	FROST	12
	FA19D6050E26SCL95	LED 8W A19 CLEAR 95 CRI 50K	120V	8	60	800	100	E26	5000K	95	CLEAR	12
	FA19D6050E26SFR95	LED 8W A19 FROST 95 CRI 50K	120V	8	60	800	100	E26	5000K	95	FROST	12

For the most up-to-date specs and warranty information, please visit www.tcpi.com

c UL us LISTED

RoHS COMPLIANT

3 YEAR WARRANTY
*Based on 12 hours use per day

High CRI Filament Lamps

	ITEM #	DESCRIPTION	VOLTAGE	WATTS	WATT EQUIV.	LUMENS	LPW	BASE	CCT	CRI	FINISH	CASE QTY.
3W Filament B11 – Dimmable • E12 Base • 15,000 Rated Life												
	FB11D2527E12SCL95	LED 3W B11 CLEAR 95 CRI 27K	120V	3	25	250	83.3	E12	2700K	95	CLEAR	12
	FB11D2527E12SFR95	LED 3W B11 FROST 95 CRI 27K	120V	3	25	250	83.3	E12	2700K	95	FROST	12
	FB11D2530E12SCL95	LED 3W B11 CLEAR 95 CRI 30K	120V	3	25	250	83.3	E12	3000K	95	CLEAR	12
	FB11D2530E12SFR95	LED 3W B11 FROST 95 CRI 30K	120V	3	25	250	83.3	E12	3000K	95	FROST	12
	FB11D2540E12SCL95	LED 3W B11 CLEAR 95 CRI 40K	120V	3	25	250	83.3	E12	4000K	95	CLEAR	12
	FB11D2540E12SFR95	LED 3W B11 FROST 95 CRI 40K	120V	3	25	250	83.3	E12	4000K	95	FROST	12
	FB11D2550E12SCL95	LED 3W B11 CLEAR 95 CRI 50K	120V	3	25	250	83.3	E12	5000K	95	CLEAR	12
	FB11D2550E12SFR95	LED 3W B11 FROST 95 CRI 50K	120V	3	25	250	83.3	E12	5000K	95	FROST	12
3W Filament B11 – Dimmable • E26 Base • 15,000 Rated Life												
	FB11D2527E26SCL95	LED 3W B11 CLEAR 95 CRI 27K	120V	3	25	250	83.3	E26	2700K	95	CLEAR	12
	FB11D2527E26SFR95	LED 3W B11 FROST 95 CRI 27K	120V	3	25	250	83.3	E26	2700K	95	FROST	12
	FB11D2530E26SCL95	LED 3W B11 CLEAR 95 CRI 30K	120V	3	25	250	83.3	E26	3000K	95	CLEAR	12
	FB11D2530E26SFR95	LED 3W B11 FROST 95 CRI 30K	120V	3	25	250	83.3	E26	3000K	95	FROST	12
	FB11D2540E26SCL95	LED 3W B11 CLEAR 95 CRI 40K	120V	3	25	250	83.3	E26	4000K	95	CLEAR	12
	FB11D2540E26SFR95	LED 3W B11 FROST 95 CRI 40K	120V	3	25	250	83.3	E26	4000K	95	FROST	12
	FB11D2550E26SCL95	LED 3W B11 CLEAR 95 CRI 50K	120V	3	25	250	83.3	E26	5000K	95	CLEAR	12
	FB11D2550E26SFR95	LED 3W B11 FROST 95 CRI 50K	120V	3	25	250	83.3	E26	5000K	95	FROST	12
4W Filament B11 – Dimmable • E12 Base • 15,000 Rated Life												
	FB11D4027E12SCL95	LED 4W B11 CLEAR 95 CRI 27K	120V	4	40	300	75	E12	2700K	95	CLEAR	12
	FB11D4027E12SFR95	LED 4W B11 FROST 95 CRI 27K	120V	4	40	300	75	E12	2700K	95	FROST	12
	FB11D4030E12SCL95	LED 4W B11 CLEAR 95 CRI 30K	120V	4	40	300	75	E12	3000K	95	CLEAR	12
	FB11D4030E12SFR95	LED 4W B11 FROST 95 CRI 30K	120V	4	40	300	75	E12	3000K	95	FROST	12
	FB11D4040E12SCL95	LED 4W B11 CLEAR 95 CRI 40K	120V	4	40	300	75	E12	4000K	95	CLEAR	12
	FB11D4040E12SFR95	LED 4W B11 FROST 95 CRI 40K	120V	4	40	300	75	E12	4000K	95	FROST	12
	FB11D4050E12SCL95	LED 4W B11 CLEAR 95 CRI 50K	120V	4	40	300	75	E12	5000K	95	CLEAR	12
	FB11D4050E12SFR95	LED 4W B11 FROST 95 CRI 50K	120V	4	40	300	75	E12	5000K	95	FROST	12
4W Filament B11 – Dimmable • E26 Base • 15,000 Rated Life												
	FB11D4027E26SCL95	LED 4W B11 CLEAR 95 CRI 27K	120V	4	40	300	75	E26	2700K	95	CLEAR	12
	FB11D4027E26SFR95	LED 4W B11 FROST 95 CRI 27K	120V	4	40	300	75	E26	2700K	95	FROST	12
	FB11D4030E26SCL95	LED 4W B11 CLEAR 95 CRI 30K	120V	4	40	300	75	E26	3000K	95	CLEAR	12
	FB11D4030E26SFR95	LED 4W B11 FROST 95 CRI 30K	120V	4	40	300	75	E26	3000K	95	FROST	12
	FB11D4040E26SCL95	LED 4W B11 CLEAR 95 CRI 40K	120V	4	40	300	75	E26	4000K	95	CLEAR	12
	FB11D4040E26SFR95	LED 4W B11 FROST 95 CRI 40K	120V	4	40	300	75	E26	4000K	95	FROST	12
	FB11D4050E26SCL95	LED 4W B11 CLEAR 95 CRI 50K	120V	4	40	300	75	E26	5000K	95	CLEAR	12
	FB11D4050E26SFR95	LED 4W B11 FROST 95 CRI 50K	120V	4	40	300	75	E26	5000K	95	FROST	12

For the most up-to-date specs and warranty information, please visit www.tcpi.com

c UL us LISTED

RoHS COMPLIANT

3 YEAR WARRANTY
*Based on 12 hours use per day