# 120-277V LED Lamps

TCP's LED Universal Voltage 120-277V Lamps are now available in A-lamps, BR30s and PAR38s shapes.

## Features & Benefits

- Up to 85% more efficient than incandescent/halogen replacements, providing instant energy savings
- PAR lamps are wet location rated for outdoor use
- Excellent color consistency and CRI

## Specifications

Color Temperatures ..... 2700K, 3000K, 3500K, 4000K, 5000K
Input Line Voltage ..... 120 VAC
Frequency ..... 50/60HZ
Lamp Life (Rated) ..... 25,000 hours
CRI ..... 80, 90
Base ..... GU5.3, GU10

| ITEM # | DESCRIPTION | VOLTAGE | WATTS | WATT EQUIV. | LUMENS | LPW | CCT | CRI | BEAM ANGLE | CBCP | CASE QTY. |
|---|---|---|---|---|---|---|---|---|---|---|---|
| **20W PAR30 – Non-Dimmable • E26 Base • 25,000 Rated Life** | | | | | | | | | | | |
| L20P30N25UNV27KFL | LED P30 HO 90 27K FL 120-277V | 120-277V | 20 | 75 | 1800 | 90.0 | 2700K | 90 | 40 | – | 12 |
| L20P30N25UNV27KNFL | LED P30 HO 90 27K NFL 120-277V | 120-277V | 20 | 75 | 1800 | 90.0 | 2700K | 90 | 25 | – | 12 |
| L20P30N25UNV30KFL | LED P30 HO 90 30K FL 120-277V | 120-277V | 20 | 75 | 1850 | 92.5 | 3000K | 90 | 40 | 2666 | 12 |
| L20P30N25UNV30KNFL | LED P30 HO 90 30K NFL 120-277V | 120-277V | 20 | 75 | 1850 | 92.5 | 3000K | 90 | 25 | 4322 | 12 |
| L20P30N25UNV40KFL | LED P30 HO 90 40K FL 120-277V | 120-277V | 20 | 75 | 1900 | 95.0 | 4000K | 90 | 40 | 2628 | 12 |
| L20P30N25UNV40KNFL | LED P30 HO 90 40K NFL 120-277V | 120-277V | 20 | 75 | 1900 | 95.0 | 4000K | 90 | 25 | 4460 | 12 |
| L20P30N25UNV50KFL | LED P30 HO 90 50K FL 120-277V | 120-277V | 20 | 75 | 1900 | 95.0 | 5000K | 90 | 40 | – | 12 |
| L20P30N25UNV50KNFL | LED P30 HO 90 50K NFL 120-277V | 120-277V | 20 | 75 | 1900 | 95.0 | 5000K | 90 | 25 | – | 12 |
| **12.5W PAR38 – Non-Dimmable • E26 Base • 25,000 Rated Life** | | | | | | | | | | | |
| L100P38N25UNV27KFL | LED 120W PAR38 UNV - 27K FLOOD | 120-277V | 12.5 | 120 | 1100 | 88 | 2700K | 80 | 40 | 2630 | 12 |
| L100P38N25UNV27KNFL | LED 120W PAR38 UNV - 27K NARROW FLOOD | 120-277V | 12.5 | 120 | 1100 | 88 | 2700K | 80 | 25 | 2613 | 12 |
| L100P38N25UNV30KFL | LED 120W PAR38 UNV - 30K FLOOD | 120-277V | 12.5 | 120 | 1100 | 88 | 3000K | 80 | 40 | 2532 | 12 |
| L100P38N25UNV30KNFL | LED 120W PAR38 UNV - 30K NARROW FLOOD | 120-277V | 12.5 | 120 | 1100 | 88 | 3000K | 80 | 25 | 2641 | 12 |
| L100P38N25UNV40KFL | LED 120W PAR38 UNV - 40K FLOOD | 120-277V | 12.5 | 120 | 1150 | 92 | 4000K | 80 | 40 | 6245 | 12 |
| L100P38N25UNV40KNFL | LED 120W PAR38 UNV - 40K NARROW FLOOD | 120-277V | 12.5 | 120 | 1150 | 92 | 4000K | 80 | 25 | 6334 | 12 |
| L100P38N25UNV50KFL | LED 120W PAR38 UNV - 50K FLOOD | 120-277V | 12.5 | 120 | 1200 | 96 | 5000K | 80 | 40 | 6412 | 12 |
| L100P38N25UNV50KNFL | LED 120W PAR38 UNV - 50K NARROW FLOOD | 120-277V | 12.5 | 120 | 1200 | 96 | 5000K | 80 | 25 | 6572 | 12 |



For the most up-to-date specs and warranty information, please visit www.tcpi.com

c UL us LISTED RoHS COMPLIANT 5 YEAR WARRANTY 3 YEAR WARRANTY

# 120-277V LED Lamps

| | ITEM # | DESCRIPTION | VOLTAGE | WATTS | WATT EQUIV. | LUMENS | LPW | CCT | CRI | BEAM ANGLE | CBCP | CASE QTY. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **24W A23 – Non-Dimmable • E26 Base • 25,000 Rated Life • Includes E26 to E39 Adapter** | | | | | | | | | | | | |
|  | L200A23N25UNV27K | LED 200W A23 UNV - 27K | 120-277V | 24 | 200 | 3000 | 125 | 2700K | 80 | OMNI | – | 48 |
| | L200A23N25UNV30K | LED 200W A23 UNV - 30K | 120-277V | 24 | 200 | 3000 | 125 | 3000K | 80 | OMNI | – | 48 |
| | L200A23N25UNV41K | LED 200W A23 UNV - 41K | 120-277V | 24 | 200 | 3000 | 125 | 4100K | 80 | OMNI | – | 48 |
| | L200A23N25UNV50K | LED 200W A23 UNV - 50K | 120-277V | 24 | 200 | 3000 | 125 | 5000K | 80 | OMNI | – | 48 |
| **18W A23 – Non-Dimmable • E26 Base • 25,000 Rated Life** | | | | | | | | | | | | |
|  | L125A23N25UNV27K | LED 125W A23 UNV - 27K | 120-277V | 18 | 125 | 2000 | 111.1 | 2700K | 80 | OMNI | – | 48 |
| | L125A23N25UNV30K | LED 125W A23 UNV - 30K | 120-277V | 18 | 125 | 2000 | 111.1 | 3000K | 80 | OMNI | – | 48 |
| | L125A23N25UNV40K | LED 125W A23 UNV - 40K | 120-277V | 18 | 125 | 2100 | 116.7 | 4000K | 80 | OMNI | – | 48 |
| | L125A23N25UNV50K | LED 125W A23 UNV - 50K | 120-277V | 18 | 125 | 2200 | 122.2 | 5000K | 80 | OMNI | – | 48 |
| **14W A21 – Non-Dimmable • E26 Base • 25,000 Rated Life** | | | | | | | | | | | | |
|  | L100A21N25UNV27K | LED 100W A21 UNV - 27K | 120-277V | 14 | 100 | 1600 | 114.3 | 2700K | 80 | OMNI | – | 48 |
| | L100A21N25UNV30K | LED 100W A21 UNV - 30K | 120-277V | 14 | 100 | 1625 | 116.1 | 3000K | 80 | OMNI | – | 48 |
| | L100A21N25UNV40K | LED 100W A21 UNV - 40K | 120-277V | 14 | 100 | 1650 | 117.9 | 4000K | 80 | OMNI | – | 48 |
| | L100A21N25UNV50K | LED 100W A21 UNV - 50K | 120-277V | 14 | 100 | 1650 | 117.9 | 5000K | 80 | OMNI | – | 48 |
| **7.5W A19 – Non-Dimmable • E26 Base • 25,000 Rated Life** | | | | | | | | | | | | |
|  | L60A19N25UNV27K | LED 60W A19 UNV - 27K | 120-277V | 7.5 | 60 | 800 | 106.7 | 2700K | 80 | OMNI | – | 48 |
| | L60A19N25UNV30K | LED 60W A19 UNV - 30K | 120-277V | 7.5 | 60 | 800 | 106.7 | 3000K | 80 | OMNI | – | 48 |
| | L60A19N25UNV40K | LED 60W A19 UNV - 40K | 120-277V | 7.5 | 60 | 850 | 113.3 | 4000K | 80 | OMNI | – | 48 |
| | L60A19N25UNV50K | LED 60W A19 UNV - 50K | 120-277V | 7.5 | 60 | 875 | 116.7 | 5000K | 80 | OMNI | – | 48 |
| **9.5W BR30 – Non-Dimmable • E26 Base • 25,000 Rated Life** | | | | | | | | | | | | |
|  | L65BR30N25UNV27K | LED 65W BR30 UNV - 27K | 120-277V | 9.5 | 65 | 900 | 94.7 | 2700K | 80 | 110 | – | 12 |
| | L65BR30N25UNV30K | LED 65W BR30 UNV - 30K | 120-277V | 9.5 | 65 | 900 | 94.7 | 3000K | 80 | 110 | – | 12 |
| | L65BR30N25UNV40K | LED 65W BR30 UNV - 40K | 120-277V | 9.5 | 65 | 925 | 97.4 | 4000K | 80 | 110 | – | 12 |
| | L65BR30N25UNV50K | LED 65W BR30 UNV - 50K | 120-277V | 9.5 | 65 | 1000 | 105.2 | 5000K | 80 | 110 | – | 12 |
| **13W BR30 – Non-Dimmable • E26 Base • 25,000 Rated Life** | | | | | | | | | | | | |
|  | L100BR30N25UNV27K | LED 100W BR30 UNV - 27K | 120-277V | 13 | 100 | 1400 | 107.7 | 2700K | 80 | 110 | – | 12 |
| | L100BR30N25UNV30K | LED 100W BR30 UNV - 30K | 120-277V | 13 | 100 | 1450 | 111.5 | 3000K | 80 | 110 | – | 12 |
| | L100BR30N25UNV40K | LED 100W BR30 UNV - 40K | 120-277V | 13 | 100 | 1500 | 115.4 | 4000K | 80 | 110 | – | 12 |
| | L100BR30N25UNV50K | LED 100W BR30 UNV - 50K | 120-277V | 13 | 100 | 1550 | 119.2 | 5000K | 80 | 110 | – | 12 |